



TYPICAL FRAME JAMB SECTION -- WITH EMBED -- 2X SCALE

OPD-2133AF 60 MINUTE FE/BR OPAQUE DOUBLE FIRE DOOR

A.F.F. = ABOVE FINISHED FLOOR
 C.O. = CLEAR OPENING
 CUST. = CUSTOMER
 D.O. = DOOR OPENING
 EXT. = EXTERIOR
 F.F. = FINISHED FRAME
 INT. = INTERIOR
 LOC. = LOCATION
 No. = NUMBER
 PO. = PURCHASE ORDER
 QTY. = QUANTITY
 R.O. = ROUGH OPENING
 V.O. = VISION OPENING
 WO. = WORK ORDER

HARDEN No. OPD-2133AF
MODEL No. GDF-60R-HSP-02A

3	1	60MIN DD OP 800	SUB FRAME
2	1	60MIN DD OP 200	L-FRAME ASSEMBLY AND WELD
1	1	60MIN DD OP 100	DOOR ASSEMBLY AND WELD
ITEM	QTY.	PART NO.	DESCRIPTION

TOLERANCES:		HARDEN ARCHITECTURAL SECURITY PRODUCTS LLC. LANCASTER, PA 17601	
ANGULAR (DEG/MIN)	±0°30'		
LINEAR (FRAC)	±1/16	CUSTOMER	
LINEAR (DEC)	.X ±.08 .XX ±.03 .XXX ±.015	TITLE	
DRAWN BY:	DATE:	OPD-2133AF 60 MIN. FE/BR / OPAQUE DOUBLE FIRE DOOR	
CHECKED BY:	DATE:	SIZE	DWG. NO. OPD-2133AF CAD REV.
ENGINEERED BY:	DATE:	SCALE	W.O. NO. SHEET